

Simple DIY draught-proofing

Ways to keep the cold air out



No-one likes to live in a draughty house. And apart from the discomfort, it's a waste of money if the heat you have paid for is escaping through gaps in the house and being replaced by cold air from outside.

The good news is that draught proofing is easy. A bit of DIY can go a long way to plugging those gaps and keeping cosy at home. You'll stop wasting money on your heating bills, and cut down on your carbon dioxide (CO₂) emissions too.

So, where do the draughts come from? Most houses, particularly old ones, have cracks and gaps through which warm air goes out and cold air blows in. Not all of these can be dealt with by a DIY-er, but many can, such as the gaps between or around floorboards; around windows and doors; through the letterbox; where pipework comes through external walls; around the loft hatch; and around electrical fittings.

For more information about draught-proofing windows, see our **secondary glazing** advice sheet. Use the checklist (right) to find out where you can draught proof different areas of your home.



Never block boiler flues, air bricks, or window trickle vents and avoid over draught-proofing windows in Kitchens and bathrooms where the moist air needs to escape.



Cutting a door brush to length

Mind the gap

The most common draught-zones ... and DIY solutions to dealing with them

Windows: Use foam, metal or plastic draught strips (see over), or brush seals for sash windows (photo, right). Temporary secondary glazing is another option



Exterior doors: Fit brush or hinged-flap draught excluders, fitted along the bottom of the doors (see over).

Interior doors: Cut draughts with 'snake' draught excluders (like the one in the photo, right), brushes or similar strips of material, (see over).



Unused chimneys: Chimney balloons are available from most DIY stores. Plastic bags stuffed with other plastic bags also work – remember to remove and let the air circulate in summer.

Around pipework: Apply silicone mastic, wall-filler or expanding foam as appropriate.

Floorboards and skirting boards: Fill the gaps with flexible fillers, clear or brown silicone mastic, decorators' caulk or similar products.



Cracks in walls: Use cement or a hard-setting decorators' wall-filler.

Redundant extractor fan outlets: These should be blocked up.

Loft hatches: Use strips of draught excluding material fitted around the edges of the frame, and don't forget to insulate the hatch itself.



Lighting and electrical fittings: Plug the gaps around the fittings with wall-filler.

Letterboxes: Fit flaps or brushes to keep the cold air out and the warm air in. See over for instructions.



See over for instructions on how to fit a door brush, how to fit a letterbox draught-excluder and how to fit draught excluding strip to a window or door

How to fit a door brush

Door brushes can be easily fitted along the bottom of most doors. First, use a tape measure to measure the width of the door and cut the brush to the right length, using a snips or a hacksaw.

Then position the brush against the door so that it just touches the floor. Using a pencil, make guide marks on the door through the pre-drilled holes in the excluder to show where the screws go.

Next drill pilot holes in the points you marked and loosely screw the excluder in place.

Open and close the door to ensure it creates a good seal before tightening the screws or adjusting the height if necessary. The excluder should not be placed so low that it catches on the floor and makes it difficult to open or close the door!



How to fit a letterbox draught-excluder

A letterbox draught-excluder is a simple way to stop warmth escaping.

First, place the draught-excluder over your letterbox mark the fixing points through the pre-drilled holes with a pencil.

Then drill pilot holes at the points you marked and loosely screw the draught-excluder onto the door, checking that letters can pass through the brushes before tightening the screws, and adjusting its position if necessary.



Fixing a perimeter seal around a window or door using foam draught-excluder

Start by cutting off a 50-60mm piece of the foam draught excluder to use as a test strip. Stick this to the door or window frame (not the door or window itself), as close as possible to the edge nearest you.

Close the door or window and slip a credit card between the test strip and the door. It should be a comfortable fit. If you have to force it, then the excluder is probably too thick; if the credit card is loose and falls out, then the excluder is probably too thin. Once you've done the test, remove the test strip.

When you're satisfied that you have the right thickness of foam excluder, measure the frame of your door or window and cut the excluder to the required lengths using a pair of scissors.

Clean and dry the door or window frame to ensure the adhesive sticks properly, then apply the foam strip to the door or window frame, as near to the edge as possible, checking that it isn't difficult to open or close the door or window!



Also available in white!



This leaflet was originally produced by the Centre for Sustainable Energy (CSE) and reprinted in this version on behalf of SEACS.

CSE's Home Energy Team offers free advice on domestic energy use to householders in Bristol and Somerset (including the unitary authorities of North Somerset and Bath & North East Somerset).


Call free on 0800 082 2234, email home.energy@cse.org.uk or follow us on twitter [@cse_homeenergy](https://twitter.com/cse_homeenergy)



3 St Peter's Court
Bedminster Parade
Bristol BS3 4AQ

0117 934 1400
www.cse.org.uk
info@cse.org.uk

We are a national charity (298740) that helps people change the way they think and act on energy.



The aim of the SEACS project is to create opportunities to reduce energy demand, improve energy efficiency and use clean, renewable energy. SEACS was selected under the European Cross-border Cooperation Programme INTERREG IV A France (Channel) – England, co-funded by the ERDF.

www.seacs.info | www.wiltshire.gov.uk/sustainability
www.dorsetforyou.com/climatechange | www.devon.gov.uk/energy